

7000SERIES



mCOMFORT SUSPENSION SEAT

Every 7000 series model comes standard with Mahindra's own mComfort Seat. Designed and manufactured in the U.S. with industry-leading comfort and support, these seats will keep you comfortable during the long days.



DELUXE CAB

The 7095 model's deluxe cab is an ergonomic master class, designed specifically for operator comfort during long workdays. Equipped with an ergonomic operator platform, USB charging port, optional buddy seat, air conditioning and heater, and much more, these deluxe cabs will make you forget you ever left your home.



COMFORTABLE OPERATOR STATION

7000 series tractors come standard with an operator station designed with easy-grip levers and handles, a clear and multifunctional instrument panel, and a lot more, ensuring everything you need is easily within site or reach when you need it.

7000 SERIES ATTACHMENTS

TRACTOR	7085 4WD	7095 4WD CAB
LOADER MODEL	7095L	7095CL
Standard Bucket Size [in]		84
Maximum Lift Height [in]		139
Dig Depth [in]		8.75
Lift Capacity to Full Height at Pivot Pin [lbs]		4200
Breakout Force [lbs]		6050
Shipping Weight [lbs]		2100



7000 SERIES SPECIFICATIONS

TRACTOR	7085 4WD	7095 4WD CAB
ENGINE		
Type	Four-stroke, Turbocharged, Direct Injection, Water Cooled Diesel Engine	
Engine HP (kW) @ RPM	85 (63.4) @ 2300	95 (70.8) @ 2300
Displacement [in ³ (cc)]	215.4 (3529)	
Number of Cylinders	4	
Bore & Stroke [in]	Bore: 3.78, Stroke: 4.8	
Fuel Tank [gal (L)]	23.7 (89.71)	
DRIVE TRAIN		
Transmission	Full Synchro Mesh with Forward / Reverse Power Shuttle & Constant Mesh Range	
Number of Speeds	15F / 15R	
Clutch	Power Shuttle with Torsional Damper (wet)	
Brakes	Oil Immersed Brakes, Disc Diameter – 8.75", Ball & Ramp Type	
PTO		
Type	2-speed Independent Single Lever PTO	
Rear PTO RPM	540/540E	
Mid PTO RPM	N/A	
PTO HP (kW)	73 (54.4)	83 (61.9)
HYDRAULICS		
Type	Open Center With Position & Draft Control	
Implement Pump Output [gpm (L/min)]	16.17 (61.2)	
Maximum Total Flow [gpm (L/min)]	21.17 (80.1)	
3-Point Hitch	CAT II w/ Telescoping Stabilizers & Flex Links	
Lift Capacity [lb (kg)]	5730 (2594)	
ELECTRICAL		
Battery	12 V, 1000 CCA	
Alternator	12 V, 55 A	12 V, 140 A
DIMENSIONS		
Overall Length [in (mm)]	167 (4241)	
Overall Width [in (mm)]	80.7 (2049)	
Overall Height [in (mm)]	105 (2667)	115 (2921)
Wheelbase [in (mm)]	94.5 (2400)	
Minimum Ground Clearance [in (mm)]	14.1 (358)	
Turning Radius [ft (m)]	13 (4)	
Weight [lb (kg)]	7450 (3379)	8380 (3801)
WHEELS & TIRES		
AG [Front/Rear]	12.4 x 24 / 18.4 x 30 Bias	12.4 x 24 / 18.4 x 30 Radial